

Beta Swift

The **Beta Swift** is a **manually-operated** table top transfer press, which is particularly suitable for laundry marking/fusing and label application, as well as general usage.

This fully portable machine can be used virtually anywhere, simply plug it in. It's unique state of the art advanced computerised controller accurately monitors both temperature and time, to make it a world leader.

Initially designed for use in the laundry industry, the Beta Swift has now been developed for more wide ranging use.

Featuring a strong, light, aluminium construction, the Swift is fitted with self-aligning spring mounted silicone pressure pad to ensure correct pressure and an audible buzzer on the timer mechanism. The simple, robust machine is powered by a microprocessor for control of both heat and dwell accuracy and ease of operation and requires minimal operating space.

Each Swift Press is produced in two versions, nominally 230-240 Volts AC for the European market and 120 Volts AC for the American market.

Specifications	European Machines
Power Consumption	500 Watts
Power Supply	230-240 Volts AC
Working temperature	70-235°C
Display Timer Range	0 - 9.59 mins
Machine height open	61 cms
Machine height closed	28 cms
Machine width	23 cms
Machine depth	47 cms
Work area required	22 x 61 x 43 cms
Weight export packed	14 kg
Size export packed	55(L) x 29(W) x 33 cms(H)
Net weight	10 kg
Press pad dimensions	13.5 x 9.5 cms
Fuses	3.15 A
A-weighted noise level	<70 dB(A)

Specifications	USA Machines
Power Consumption	500 Watts
Power Supply	120 Volts AC
Working temperature	160-455°F
Display Timer Range	0 - 9.59 mins
Machine height open	24 ins
Machine height closed	11 ins
Machine width	9 ins
Machine depth	18.5 ins
Work area required	8.6 x 24 x 17 ins
Weight export packed	31 lbs
Size export packed	21.5(L) x 11.5(W) x 13 ins(H)
Net weight	22 lbs
Press pad dimensions	5.25 x 3.75 ins
Fuses	6.3 A
A-weighted noise level	<70 dB(A)